

# SPECIALS

Hand Scraped

## Specials Kinabalu

1204342

220 x 22 cm  
15/4 mm

CE  
EN 14342-05



### Packaging

Boards per pack:	6 boards
m <sup>2</sup> per pack:	2,904 m <sup>2</sup>
Weight per pack:	23 kg
Broken lengths per pack:	25% minimal 60 cm length

### Dimensions

Length:	220 cm
Width:	22 cm
Thickness (total):	15 mm
Top layer:	3,5-4,0 mm

### Dimensional tolerances according to EN13489

Length:	0,20%
Width:	0,2 mm
Thickness:	Total: 15 mm ± 0,2 mm
Top layer:	3,5-4,0 mm
Height difference between the panels:	≤0,2 mm
Squareness:	≤0,2% across the width
Cup:	≤0,2% across the width
Spring:	≤0,1% over the length
Bend:	≤1% over the length

### Other Specifications

Formaldehyde emission:	E1
Insulation value:	R=0,115m <sup>2</sup> k/w
Brinell hardness:	Average HB 3.7

### Additional specifications

Bevel:	Rounded
Construction:	3-layerd
Moisture content:	7% +/- 2%
Locking system:	Tongue and groove

### Instructions and Maintenance

Oil immediately after installation.  
Maintain with Solidfloor™ Ultimate Hardwax White & Solidfloor™ Woodcleaner. Suitable for underfloor heating & cooling (visit [www.solidfloor.com](http://www.solidfloor.com) for more information).



EN 14342-05